









Quick-Finder Stainless steel/Protection against dust and water splashes

Read-out [d] g	Weighing range [Max] kg	Model KERN	Price excl. of VAT ex works	 1 DAY							
0,1	0,5	FOB 500-1S	79,-	1		•				•	
0,1	0,5	FOB 0.5K-4NS	105,-	1		•			•	•	
0,2	1,5	WTB 1K-4N	215,-	1		•		•	•		•
0,2	1,5	FFN 1K-4N	260,-	1		•		•	•	•	•
0,2	3	FOB 3K 4NL	265,-	1		•		•	•	•	
0,5	1,5	FOB 1.5K0.5	180,-	1		•		•	•	•	•
0,5	1,5	FOB 1K-4LM	265,-	1		•		•	•	•	•
0,5	1,5	WTB 1K-4NM	250,-	1	•	•		•	•	•	•
0,5	1,5	FFN 1K-4NM	285,-	1	•	•		•	•	•	•
0,5	3	WTB 3K-4N	215,-	1		•		•	•	•	•
0,5	3	FFN 3K0.5IPN	255,-	1		•		•	•	•	•
0,5	3	FXN 3K-4N	280,-	1		•		•	•	•	•
0,5 1	5 7,5	FOB 7K-4NL	230,-	1		•		•	•	•	
1	3	FOB 3K1	180,-	1		•		•	•	•	•
1	3	FOB 3K-3LM	265,-	1		•		•	•	•	•
1	3	WTB 3K-3NM	250,-	1	•	•		•	•	•	•
1	3	FFN 3K1IPM	285,-	1	•	•		•	•	•	•
1	3	FXN 3K-3M	340,-	1		•		•	•	•	•
1	5	FOB 5K1S	79,-	1		•		•	•	•	
1	5	FOB 5K-3NS	105,-	1		•		•	•	•	
1	6	WTB 6K-3N	215,-	1		•		•	•	•	•
1	6	FFN 6K1IPN	255,-	1		•		•	•	•	•
1	6	FXN 6K-3N	280,-	1		•		•	•	•	•
1	10	SFB 10K1HIP	670,-	1		•	•	•	•	•	•
1 2	3 6	SXS 6K-3M	670,-	1	•	•	•	•	•	•	•
1 2	8 15	FOB 10K-3NL	230,-	1		•		•	•	•	
2	6	FOB 6K2	180,-	1		•		•	•	•	•
2	6	WTB 6K-3NM	250,-	1	•	•		•	•	•	•
2	6	FFN 6K2IPM	285,-	1	•	•		•	•	•	•
2	6	FXN 6K-3M	340,-	1		•		•	•	•	•
2	15	WTB 10K-3N	215,-	1		•		•	•	•	•
2	15	FFN 15K2IPN	255,-	1		•		•	•	•	•
2	15	FXN 10K-3N	280,-	1		•		•	•	•	•
2	20	SFB 20K2HIP	670,-	1		•	•	•	•	•	•
2 5	6 15	SXS 10K-3M	670,-	1	•	•	•	•	•	•	•
2 5	6 15	SXS 10K-3LM	820,-	1	•	•	•	•	•	•	•
2 5	16 30	FOB 30K-3NL	230,-	1		•		•	•	•	
5	15	FOB 10K-3LM	265,-	1	•	•		•	•	•	•
5	15	WTB 10K-3NM	250,-	1	•	•		•	•	•	•
5	15	FFN 15K5IPM	285,-	1	•	•		•	•	•	•
5	15	FXN 10K-3M	340,-	1		•		•	•	•	•
5	15	SFB 15K5HIPM	690,-	1	•	•	•	•	•	•	•
5	25	FFN 25K5IPN	255,-	1		•		•	•	•	•
5	30	WTB 30K-3N	215,-	1		•		•	•	•	•
5	30	FXN 30K-3N	280,-	1		•		•	•	•	•
5	50	SFB 50K5HIP	670,-	1		•	•	•	•	•	•
5	50	SFB 50K5LHIP	740,-	1		•	•	•	•	•	•
5	50	SFB 50K-3XL	870,-	1		•		•	•	•	•
5 10	15 30	SXS 30K-2M	820,-	1	•	•	•	•	•	•	•
5 10	15 30	SXS 30K-2LM	1110,-	1	•	•	•	•	•	•	•
10	25	FFN 25K10IPM	285,-	1	•	•		•	•	•	•
10	30	WTB 30K-2NM	250,-	1	•	•		•	•	•	•
10	30	FXN 30K-2M	340,-	1		•		•	•	•	•
10	30	SFB 30K10HIPM	690,-	1	•	•	•	•	•	•	•
10	100	SFB 100K10HIP	730,-	1		•	•	•	•	•	•
10	100	SFB 100K-2XL	1140,-	1		•	•	•	•	•	•
10 20	30 60	SXS 60K-2M	820,-	1	•	•	•	•	•	•	•
10 20	30 60	SXS 60K-2LM	1110,-	1	•	•	•	•	•	•	•
20	60	SFB 60K-2XLM	1010,-	1		•	•	•	•	•	•
20 50	60 150	SXS 100K-2M	1110,-	1	•	•	•	•	•	•	•
20 50	60 150	SXS 100K-2LM	1370,-	1	•	•	•	•	•	•	•
50	150	SFB 100K-2HM	760,-	1	•	•	•	•	•	•	•
50	150	SFB 100K-2XLM	1150,-	1	•	•	•	•	•	•	•
50 100	150 300	SXS 300K-2M	1370,-	1	•	•	•	•	•	•	•

• = standard ○ = option



Package shipment

The time required for internal shipping preparations is shown in days in the pictogram



Verification possible



Adjusting program CAL

For quick setting up of the balance's accuracy. External adjusting weight required



Data interface RS-232

To connect the balance to a printer, PC or network



Weighing with tolerance range

(Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model



Protection against dust and water splashes IPxx



Stainless steel

The balance is protected against corrosion



Rechargeable battery pack

Rechargeable set