


Quick-Finder – Floor Scale

| Readout [d]: | Weighing range | Weighing plate (mm) | Model | Delivery time (day) |  | | | | | | | | | | |
|--------------|----------------|---------------------|----------------|---------------------|--|---------|--------|--------|-----|-----|------|----|------|------|--|
| | | | | | M (+7 DAYS) | CAL EXT | MEMORY | RS 232 | PCS | TOL | MOVE | IP | INOX | ACCU | |
| 100/200 g | 300/600 kg | 1000x1000 | BIC 600K-1S | 2 | | ■ | | | | | | ■ | | | |
| 100/200 g | 300/600 kg | 1500x1200 | BIC 600K-1 | 2 | | ■ | | | | | | ■ | | | |
| 100/200 g | 300/600 kg | 1000x1000 | BID 600K-1DSM | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 100/200 g | 300/600 kg | 1500x1200 | BID 600K-1SM | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 200 g | 600 kg | 1000x1000 | BID 600K-1SM | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 200 g | 600 kg | 1500x1200 | BID 600K-1M | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 200 g | 600 kg | 1000x1000 | BFB 600K-1SNM | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 200 g | 600 kg | 1500x1250 | BFB 600K -1NM | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 200 g | 600 kg | 1000x1000 | BFA 600K-1SNM | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 200 g | 600 kg | 1500x1250 | BFA 600K-1SNM | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 200 g | 600 kg | 1000x1000 | BXS 600K-1SM | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 200 g | 600 kg | 1500x1250 | BXS 600K-1M | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 200 g | 600 kg | 1000x1000 | BFN 600K-1SM | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ■ | |
| 200 g | 600 kg | 1000x1000 | BKN 600K-1SM | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 200 g | 600 kg | 1500x1250 | BKN 600K-1M | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 200 g | 600 kg | 2*800x120 | UFA 600K-1S | 2 | | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 200 g | 600 kg | 1190x840 | UIB 600K-1 | 2 | | ■ | | | | | ■ | ■ | | | |
| 200 g | 600 kg | 1190x840 | UFB 600K200M | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 200 g | 600 kg | 1190x840 | UFN 600K200IPM | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 200 g | 600 kg | 1600x1200 | NFB 600K200M | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 200 g | 600 kg | 1800x1400 | NFB 600K200LM | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 200 g | 600 kg | 1600x1200 | NFN 600K-1M | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 200/500 g | 600/1500 kg | 1000x1000 | BIC 1T-4S | 2 | | ■ | | | | | | ■ | | | |
| 200/500 g | 600/1500 kg | 1500x1250 | BIC 1T-4 | 2 | | ■ | | | | | | ■ | | | |
| 200/500 g | 600/1500 kg | 1000x1000 | BID 1T-4DSM | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 200/500 g | 600/1500 kg | 1500x1200 | BID 1T-4DM | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 500 g | 1500 kg | 1000x1000 | BID 1T-4SM | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 500 g | 1500 kg | 1200x1000 | BID 1T-4EM | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 500 g | 1500 kg | 1500x1200 | BID 1T-4M | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 500 g | 1500 kg | 1000x1000 | BFB 1T-4SNM | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 500 g | 1500 kg | 1500x1250 | BFB 1T-4NM | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 500 g | 1500 kg | 1000x1000 | BFA 1T-4SNM | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 500 g | 1500 kg | 1500x1250 | BFA 1T-4NM | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 500 g | 1500 kg | 1000x1000 | BXS 1.5T-4SM | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 500 g | 1500 kg | 1500x1250 | BXS 1.5T-4M | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 500 g | 1500 kg | 1000x1000 | BFN 1T-4SM | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ■ | |
| 500 g | 1500 kg | 1495x1245 | BFN 1.5T-0.5M | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ■ | |
| 500 g | 1500 kg | 1000x1000 | BKN 1T-4SNM | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 500 g | 1500 kg | 1500x1250 | BKN 1T-4M | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 500 g | 1500 kg | 2*1270x170 | UFA 1.5T-0.5 | 2 | | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 500 g | 1500 kg | 1190x840 | UIB 1.5T-4 | 2 | | ■ | | | | | ■ | ■ | | | |
| 500 g | 1500 kg | 1190x840 | UFB 1.5T0.5M | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 500 g | 1500 kg | 1300x842 | UFC 1T-1M | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | | ○ | |
| 500 g | 1500 kg | 1190x840 | UFN 1.5T0.5IPM | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ■ | |
| 500 g | 1500 kg | 1600x1200 | NFB 1.5T0.5M | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 500 g | 1500 kg | 1800x1400 | NFB 1.5T0.5LM | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 1000 g | 1500 kg | 1600x1200 | NFN 1.5T-4M | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ | |
| 500 g/1 Kg | 1.5 / 3 t | 1500x1200 | BIC 3T-3 | 2 | | ■ | | | | | | ■ | | | |
| 500 g/1 Kg | 1.5 / 3 t | 1500x1500 | BIC 3T-3L | 2 | | ■ | | | | | | ■ | | | |
| 500 g/1 Kg | 1.5 / 3 t | 1500x1200 | BID 3T-3DM | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 500 g/1 Kg | 1.5 / 3 t | 1500x1500 | BID 3T-3DLM | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 1 Kg | 3000 kg | 1500x1200 | BID 3T-3M | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 1 Kg | 3000 kg | 1500x1500 | BID 3T-3LM | 2 | ○ | ■ | ○ | ■ | ■ | ■ | ■ | ■ | | | |
| 1 Kg | 3000 kg | 1500x1250 | BFB 3T-3NM | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |
| 1 Kg | 3000 kg | 1500x1500 | BFB 3T1LM | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ | |

| | | | | | | | | | | | | | | |
|------|---------|------------|------------|---|---|---|---|---|---|---|---|---|---|---|
| 1 Kg | 3000 kg | 1500x1250 | BFA 3T-3NM | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ |
| 1 Kg | 3000 kg | 1500x1500 | BFA 3T-3LM | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ |
| 1 Kg | 3000 kg | 1500x1250 | BXS 3T-3M | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ |
| 1 Kg | 3000 kg | 1500x1250 | BFN 3T-3M | 2 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ |
| 1 Kg | 3000 kg | 1500x1250 | BKN 3T-3M | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ |
| 1 Kg | 3000 kg | 1500x1500 | BKN 3T-3LM | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ |
| 1 Kg | 3000 kg | 2*1270x175 | UFA 3T1 | 2 | | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ |
| 1 Kg | 3000 kg | 2*2100x160 | UFA 3T-3L | 2 | | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ |
| 1 Kg | 3000 kg | 1190x840 | UIB 3T-3 | 2 | | ■ | | | | ■ | ■ | | | |
| 2 Kg | 6000 kg | 1500x1500 | BFB 6T-3M | 2 | ○ | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ |
| 2 Kg | 6000 kg | 1500x1500 | BFS 6T-3M | 5 | ○ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | | ○ |
| 2 Kg | 6000 kg | 11500x1500 | BFA 6T-3M | 5 | ○ | ■ | | ○ | ■ | ■ | ■ | ■ | ■ | ○ |
| 2 Kg | 6000 kg | 2*2000x120 | UFA 6T-3 | 2 | | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ |
| 2 Kg | 6000 kg | 2*2100x160 | UFA 6T-3L | 2 | | ■ | | ■ | ■ | ■ | ■ | ■ | | ○ |



Package shipment

The time required for internal shipping preparations is shown in days in the pictogram



Verification possible



Adjusting program CAL

For quick setting up of the balance's accuracy. External adjusting weight required



Memory

Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.



Data interface RS-232

To connect the balance to a printer, PC or network



Piece counting:

Reference quantities selectable. Display can be switched from piece to weight



Weighing with tolerance range

(Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model



Hold function:

(Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value



Protection against dust and water splashes IPxx:

The type of protection is specified in the datas.



Stainless steel:

The balance is protected against corrosion



Battery operation

Ready for battery operation. The battery type is specified for each device