








Quick-Finder Price computing scales

Read-out [d] g	Weighing range [Max] kg	Model	Price excl. of VAT ex works €	 1 DAY	 M	 CAL EXT	 RS 232	 MEMORY	 IP 6	 ACCU
1 2	3 6	RIB 6K-3M	205,-	1	○	●		●		○
1 2	3 6	RIB 6K-3HM	235,-	1	○	●		●		○
1 2	3 6	RPB 6K1DM	205,-	1	○	●	●	●		○
1 2	3 6	RPB 6K1DHM	220,-	1	○	●	●	●		○
1 2	3 6	RFE 6K3M	280,-	1	○	●	●	●		○
2 5	6 15	RIB 10K-3M	205,-	1	○	●		●		○
2 5	6 15	RIB 10K-3HM	235,-	1	○	●		●		○
2 5	6 15	RPB 15K2DM	205,-	1	○	●	●	●		○
2 5	6 15	RPB 15K2DHM	220,-	1	○	●	●	●		○
2 5	6 15	RFE 15K3M	280,-	1	○	●	●	●		○
5 10	15 30	RIB 30K-2M	205,-	1	○	●		●		○
5 10	15 30	RIB 30K-2HM	235,-	1	○	●		●		○
5 10	15 30	RPB 30K5DM	205,-	1	○	●	●	●		○
5 10	15 30	RPB 30K5DHM	220,-	1	○	●	●	●		○
5 10	15 30	RFE 30K3M	280,-	1	○	●	●	●		○

● = standard ○ = option



Package shipment

The time required for internal shipping preparations is shown in days in the pictogram



Verification possible



Adjusting program CAL

For quick setting up of the balance's accuracy. External adjusting weight required



Data interface RS-232

To connect the balance to a printer, PC or network



Memory

Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.



Protection against dust and water splashes IPxx



Rechargeable battery pack

Rechargeable set